



Product Specifications

Printing Method	Thermal Transfer, Spot Color
Print Stations	2 independent; Two-Sided Printing (<i>1 on the front and 1 on the back</i>)
Resolution	304 dpi
Maximum Print Width	4.4" (112 mm) from the inside (left) edge of label
Maximum Print Length	44" (111.8 cm) with Windows® Printer Driver; 22" (55.9 cm) with Custom QuickLabel®
Print Speed	2" (50 mm) –5" (127 mm) per second
Resident Barcodes	All Standard, including 2-D
Fonts	7 TrueType resident; other TrueType fonts can be downloaded
Control Panel	Ergonomic keypad, backlit LCD display and menu functions
Connectivity/Data Interface	PC and AS/400. Parallel (<i>centronics</i>) & Serial (<i>RS-232 & RS-422</i>)
Software	Windows® Vista/XP/2000/2003 Server Driver Printer Drivers included; Custom QuickLabel® Label Creation Suite Optional
Halftoning	MicroCell™ - Individually selectable halftoning for each <i>object</i> ; coarse, medium, fine, error diffusion, & photographic.
Memory	128 Mb RAM; 512 Mb FLASH Memory Card included; Up to 2 Gb FLASH Memory Card <i>Optional</i>
Dimensions	20" (508 mm) H x 17" (432 mm) D x 22" (559 mm) L
Weight	84 lbs. (38 kg) - <i>no media, no ribbons</i>
Power Requirements	110/240 VAC, 50/60 Hz, 400W

RIBBONS & LABELS

Thermal Transfer Ribbon Supply	984 ft (300 m) length rolls
Thermal Transfer Ribbon Standard Widths	1.75" (45 mm), 2" (57 mm), 2.75" (70 mm), 3.25" (83 mm), 3.75" (96 mm), 4.25" (108 mm), 4.75" (121 mm)
Maximum Label Width	4.625" (117 mm)
Minimum Label Width	1" (25 mm)
Minimum Label Length	.395" (10 mm)
Label/Tag Thickness	.012" (.305 mm)
Label/Tag Roll Capacity	10" (254 mm) Outside Diameter maximum
GAP	
Maximum Gap Size	3.9" (99 mm)
Minimum Gap Size	0.07874" (2 mm)
Black Reflective Mark	
Maximum Reflective Mark Size	3.9" (99 mm)
Minimum Reflective Mark Size	0.07874" (2 mm)
Minimum Length of Reflective Mark Extending from Inside Edge of Media	.47" (12 mm)



The Labels You Want When You Need Them®

World Headquarters

600 East Greenwich Avenue, West Warwick, Rhode Island 02893

401.828.4000 / toll free 1.877.757.7978

E-mail: info@QuickLabel.com

Web site: www.QuickLabel.com

©2009 QuickLabel Systems, An Astro-Med, Inc. brand
Specifications subject to change at anytime without notice.